

71534 U.S. PTO



04/30/97

PATENT, TRADEMARK AND
COPYRIGHT CAUSES
LOUIS WEINSTEIN, P.C.*
LISA B. SCHER**

* MEMBER PA, NJ & NY BARS
** MEMBER PA & DC BARS

LAW OFFICES

Weinstein, Scher & Kimmelman

SUITE 750

THE CURTIS CENTER

601 WALNUT STREET

PHILADELPHIA, PENNSYLVANIA 19106

(215) 928-4730



08848841

68340 U.S. PTO

NELSON E. KIMMELMAN
(1922-1986)

TELECOPIER: (215) 928-4736

EXPRESS MAIL NO. EM456968096US
MAILED: APRIL 30, 1997

Hon. Commissioner of Patents and Trademarks
Washington, D.C. 20231
BOX PATENT APPLICATION

FILE NO. : BISTRACK 3.0-002 CIP CIP CIP
INVENTOR(S) : CARL BISTRACK
TITLE : ADAPTABLE PRESSURE WRITING INSTRUMENT
HOLDER

Dear Sir:

Enclosed herewith please find the following documents in the above-identified application for Letters Patent of the United States:

- 1 Pages of Abstract
- 42 Pages of Specification
- 38 Number of Claims
- 21 Sheets of Drawings (Formal)
- YES Declaration, Power of Attorney, and Petition
- YES Verified Statement Claiming Small Entity Status
- NO Assignment for Recording (attached to a copy of this letter)
- YES One (1) Return-Addressed Postcard
- NO Preliminary Amendment
- NO Request for Permission to Amend the Figures
- NO Information Disclosure Statement

Check No. 6728 in the amount of \$ 703.00 calculated as follows:

Basic Fee (\$385/\$770).....\$ 385.00
Additional Fees:
Total Number of Claims: 38
Total Number of Claims in Excess of 20, 18 x (\$11/\$22).. 198.00

Number of Independent Claims: 6
Number of Independent Claims Minus 3, 3 x (\$40/\$80)... 120.00

Assignment Recording Fee (\$40.00)..... .00
Multiple Dependent Claims (\$130/\$260)..... .00

TOTAL FILING AND ASSIGNMENT RECORDING FEES \$ 703.00

703-201

60640-7484880

I hereby certify that this correspondence is being deposited with the United States Postal Service as EXPRESS MAIL in an envelope addressed to: Commissioner of Patents and Trademarks, Washington, D.C. 20231 on: April 30, 1997
Date of Deposit
Signature L. Bistrack

PAGE 2

FILE NO.: BISTRACK 3.0-002 CIP CIP CIP

CONVENTION DATE:

Priority Documents: _____ Enclosed _____ Will Follow


No Convention Priority is Claimed.

The Commissioner is hereby authorized to charge any fees which may be required, or any deficiencies that may arise in connection with this application or to credit any overpayments which may be owed to Applicant, to our Deposit Account No. 23-0815.

Should any questions arise as to fees or deficiencies, as well as to any other matters concerning this application, please communicate with our Washington associate, Morton J. Rosenberg, Esq., Telephone: 301-465-6678.

Respectfully submitted,

WEINSTEIN, SCHER & KIMMELMAN

By 
Louis Weinstein
Registration No. 20,477
The Curtis Center
601 Walnut Street
Suite 750
Philadelphia, PA 19106
Phone: 215-928-4730

LW/rb
Enclosures

036434-0409

(BISTRACK 3.0-002 CIP CIP CIP)

ADAPTABLE PRESSURE WRITING INSTRUMENT HOLDER

CROSS-REFERENCE TO RELATED APPLICATIONS

5 The present application is a continuation-
in-part application of U. S. Application Serial No.
08/237,552, filed May 3, 1994, which is a
continuation-in-part application of U. S.
Application Serial No. 07/968,210, filed October 29,
10 1992, which is a continuation-in-part application of
U. S. Application Serial No. 07/652,067, filed
February 7, 1991, now abandoned.

FIELD OF THE INVENTION

15 This invention relates to hand held
writing instrument holders, more specifically to
those holders designed for persons with writing
disabilities and handicaps, and that offer, to both
handicapped and normal persons more writing comfort
and alternative methods of holding and applying
20 minimal pressure control to a narrow or wide
instrument other than the conventional use of
significant pressing forces applied by the thumb,
index and middle finger of the gripping hand.

BACKGROUND OF THE INVENTION

25 There are many people who have difficulty
holding and using writing instruments or cannot use
them because of limited, varying, or minimal hand or
finger gripping ability. This may be the result of
a number of conditions ranging from brain impairment
to severe cases of arthritis of the hand, digital
30 deformities, missing fingers, or merely a single

sprained, cut, broken or a mild or severe cramped finger or hand or group of fingers. Hand injuries are very common among younger persons, as is arthritis to the older population. Also the pain due to arthritis or conditions such as Tendinitis, Carpal Tunnel Syndrome, Multiple Sclerosis, Cerebral Palsy, and Brain or spinal chord injury makes holding conventional writing instruments very difficulty, if not impossible.

It has been found through research that arthritis, or inflammation of the joints is the most common condition affecting people in the United States. Inflammation of the finger joints will affect functionality to varying degrees from a mild pain causing discomfort from the prolonged holding and use of a writing or other instrument, to the more severe form of arthritis which may cause a deformity of the fingers rendering them misshapen for conventional use in grasping or holding a narrow diameter object using the conventional three fingers to apply direct pressure to the instrument for the control of the instrument. Due to the wide range of user's needs it is not an easy or practical task to design a device which will take into account the variety and shapes of support needed to accommodate every instance of hand or finger injury or deformity.

The field of Ergonomics in the workplace is emerging, fueled by workers compensation claims for injuries to the wrist, hand and fingers. One Ergonomics objective is to make the tool fit the worker, and not force-fit the worker to the tool. Simultaneously, research institutions, private and governmental, are discovering underlying causes of Musculoskeletal difficulties. The nature of

Repetitive Stress Injuries is just now being understood. It has been suggested that arthritis of the hand, for instance, may be as a result of the incorrectly shaped tools we use over a long period of time; and not necessarily a function of "Old Age" as previously thought. Ergonomics is uncovering and changing many such beliefs. The focus now is to recognize harmful work/play habits and change the tools we use to make them more adaptable and comfortable for use.

No such device has been made readily available for every day use, nor is there a device that gives the appearance of a prosthetic device used by "cripples", that is simple and common, that is inexpensive to manufacture, to the extent that it might be a "use and throw away" off-the-shelf disposable item, as common as a pen or pencil which is gripped by the device.

A number of devices have been patented which resolve a very specific comfort range, or type or impairment or designated task such as:

"Implement Holding Cuff" by Bischoff et al. U. S. Pat. No. 4,602,885, July 1986, which is designed for the physically handicapped and will contain a hand, fingers, and instrument within a controllable cage or cuff to cradle a non-functioning hand.

"Rolling Support for Writing Instruments" of Russell A. Schroeder, Jr., U. S. Pat. No. 2,497,418, February 1950, whose rolling hand rest writing device must be in contact with the writing surface, is not a hand held device, and concentrates on persons with total digital impairment or hand paralysis, shifting the emphasis to arm and shoulder control to provide the ability to write.

The J. F. Hume, U. S. Pat. No. 1,438,114, December 1922, "Writing Implement" comprising a whole hand palm size sliding ball with embedded pen designed to teach proper penmanship while supporting the hand, and which assumes that normal digital control exists.

The patent of H. G. Eastman, Pat. No. 78,655, issued June 1868, "Improvement In Pen Holders" employs a unique egg-shaped palm rest coupled with slip-in finger holders for the correct positioning of the pen, but the design does not provide for pressure of the palm to aid in the writing process, nor for non-finger use, or for gripping the instrument other than by conventional methods.

The "Tool Holding Appliance" Winter et al., U. S. Pat. No. 4,606,484, issued August 19, 1986 utilizes a device which is strapped on to the palm of the hand and holds very specifically designed tools and utensils and is intended for persons with limited hand mobility. A more significant invention in this field by Brody, Pat. No. 4,523,781, issued June 18, 1985 was specifically designed for those persons suffering from arthritis and others having reduced gripping ability. Brody's device, a palm size, barrel-shaped, clam-shell-type instrument holder is meant to be held and manipulated within the palm of the hand, and when a user lacks any digital dexterity, the device can be strapped onto the hand. Brody's design assumes that a normal "palm" or open palm does exist and has limited application for controlled downward pressure other than through the attachable hand strap or gripping of the barrel, and does not make allowances for: more adaptable hand positioning as the

individual deformity may require for comfort or for unorthodox use of those parts of the hand such as the "V" joints between fingers; or the palm and inner finger joint only, without the use of the actual fingers; or the use of any two desired fingers however closely or widely spaced; or unbending fingers that may still be usable for downward pressure and control of a writing instrument.

There are other numerous patented writing instrument holders which tie on, strap on, or slip on or through, but each such holder is designed to overcome a specific infirmity or add a degree of ease and comfort. Based on prior art known to this inventor, no hand-held writing instrument holder is available that has the adaptability of my writing instrument holder, or offers the many simultaneous combinations as is needed by the user, the many compound vertical, horizontal, bevelled, rounded, concave, convex or volute surfaces for variable open-finger grasping positions, or degree of control from parts of the finger exerting pressure and manipulation, or the capability of using the palm of the hand in conjunction with an opposing member in an unorthodox manner for holding and guiding a writing instrument or other type of instrument, providing the restoration of writing abilities, even though minimal prehensile ability exists and absolutely unorthodox highly individualized methods are called for and employed.

It is also important to provide an instrument holder for use by persons having normal holding and writing skills which reduces the gripping forces required to manipulate conventional instruments and which reduces the discomfort,

fatigue and/or pain encountered in the performance of repeated operations.

OBJECTS OF THE INVENTION

5 An object of my invention is to provide a writing instrument holder designed to lend advantage to those not having full use of their hands and fingers, to offer a constant variety of alternative compound surfaces, and simultaneous combinations and options in applying pressure and control to a
10 writing instrument other than the conventional combined use of the thumb, index and middle finger of the writing hand pressed against an instrument in a tight grip pattern.

15 Another object is to provide an instrument holder which conforms to the individual's hand and varying methods of applying controlling pressure thereto, however unorthodox, and being accomplished through the design, materials and construction thereof.

20 Another object of my invention is to provide an everyday readily attainable and personal answer through the use of this invention to temporary writing disabilities such as finger and hand cramps, sprains or fractures in splints or hand
25 casts.

30 Still another object of the present invention is to provide a holding device which is simple to use, which may be gripped in a variety of different ways and which optimally minimizes the pressing forces typically used to hold and manipulate an instrument.

Another object of the present invention is to incorporate all working surfaces of an adaptable

pressure pencil grip into a complete writing instrument or other stylus-like tool or instrument. By incorporating these surfaces into the writing instrument or tool itself, the user will no longer have the task of having to push or pull the slip-on grip for positioning, which may be difficult for those persons with finger difficulties.

Another object of the of the present invention is to provide a long comfort groove which will form-fit any finger or member, and orient the finger position along the side of the instrument barrel.

Another object of the present invention is to link the comfort-grooved barrel with the contoured finger saddle, providing a comfortable and secure resting place on the downward pressure surface.

Another object of the present invention is to provide a combination of surfaces adaptable to the users needs at any one time, that may be easily interchanged as the user might wish for writing or tool positioning, comfort, or pressure application or merely change as desired.

Another object of the present invention is to provide multiple surfaces for adaptability to those persons with missing, sprained, broken or arthritic fingers who may wish to use a writing instrument an a highly personal configuration to their advantage.

Other objects advantages and novel features will become apparent from the detailed descriptions and the accompanying drawings.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 shows a right side view of instrument holder.

Figure 1A shows an instrument holder in use by right handed person indicating hand, palm and finger position options.

Figure 2 shows a front view of instrument holder.

Figure 3 shows a top view of instrument holder.

Figure 3A shows a top view of instrument holder with hand in position indicating palm rest, and upper and lower finger shelves.

Figure 4 shows a left side of instrument holder.

Figure 4A shows a left side view with hand in position.

Figure 4B shows a left side view, another alternate method of grasping the instrument holder at the concave contoured surface showing that full instrument use can be accomplished using only the pressure applied from the inner thumb and base of the index finger, or webbing between finders. NO actual finder pressure is needed for the use of the instrument.

Figure 5 shows a back view of instrument holder.

Figure 6 shows a reverse view, alternate method of grasping instrument holder. Holder and writing instrument are shown in an upside down position, the writing instrument reversed. In this position downward pressure of the palm of the hand is used to accomplish control of the instrument in conjunction with wrist or finger guidance, or minimum pressure from the inner thumb and base of the index finger. No actual finder pressure is

needed for the use of the instrument in this position.

Figure 7 is a front elevation view of a second exemplary embodiment of the invention.

5 Figure 7A shows a hand gripping the device shown in Figure 7.

Figure 8 is a side elevation view of the device shown in Figure 7.

10 Figure 8A shows a hand gripping the device shown in Figure 8.

Figure 9 is a rear elevation view of the device shown in Figure 7.

Figure 9A shows a hand gripping the device shown in Figure 9.

15 Figure 10 is a plan view of the device shown in Figure 7.

Figure 11 is a front elevation view of a third exemplary embodiment of the invention.

20 Figure 11A is a side elevation view of a device as shown in Figure 7, modified to form the device shown in Figure 11.

Figure 12 is a side elevation view of the device shown in Figure 11.

25 Figure 13 is a rear elevation view of the device shown in Figure 11.

Figure 14 is a front elevation view of a fourth exemplary embodiment of the invention.

Figure 15 is a side elevation view of the device shown in Figure 14.

30 Figure 15A shows a hand holding the device shown in Figure 15.

Figure 16 is a plan view of the device shown in Figure 14.

35 Figure 16A shows a hand holding the device shown in Figure 16.

2025 RELEASE UNDER E.O. 14176

Figure 17 is a side elevation view of a fifth exemplary embodiment of the invention.

Figure 17A shows a hand holding the device shown in Figure 17.

5 Figure 18 is a front elevation view of the device shown in Figure 17.

Figure 19 is a rear elevation view of the device shown in Figure 17.

10 Figure 20 is a plan view of the device shown in Figure 17.

Figure 21 is a side elevation view of a sixth exemplary embodiment of the invention.

Figure 21a shows a hand holding the device shown in Figure 21.

15 Figure 21b is a plan view of the device shown in Figure 21.

Figure 22 shows a variation of the embodiment shown in Figure 21.

20 Figure 23 is a perspective view of still another embodiment of a holding device incorporating the principles of the present invention and showing the manner in which an instrument is supported thereby.

25 Figure 23A shows one arrangement for holding the device of Figure 23 by a right hand of an operator.

Figure 23B shows another arrangement for holding the device of Figure 23 utilizing a left hand of an operator.

30 Figure 23C shows still another arrangement for holding the device of Figure 23 utilizing a right hand.

35 Figure 23D shows still another manner in which the holding device of Figure 23 may be gripped by a left hand.

03848844.043092

Figure 24 is a front elevational view of the holding device of Figure 23.

Figure 25 is a rear elevational view of the holding device of Figure 23.

5 Figure 26 is a top view of the holding device of Figure 23.

Figure 27 is a perspective view showing a modification of the embodiment of Figure 23.

10 Figure 28 shows a three-quarter perspective of still another preferred embodiment of the present invention comprising a writing instrument having an integral holding device.

15 Figure 28A is a view of the embodiment of Figure 28 showing a fingertip applying pressure to finger saddle of the integrated holding device.

Figure 28B shows a view of the embodiment of Figure 28 showing a thumb applying pressure to the finger saddle of the integrated holding device.

20 Figure 28C is a view showing a middle finger knuckle applying pressure to the finger saddle of the integrated holding device.

Figure 29A is a side view showing the offset manner in which the ink/lead supply is arranged and showing the retainer cap.

25 Figure 29B shows an enlarged view of the retainer cap of Figure 29.

Figure 29C is a view of the cover cap for the instrument shown in Figure 29A.

30 Figure 30 shows a front view of the embodiment of Figure 28.

DETAILED DESCRIPTION OF THE INVENTION
AND PREFERRED EMBODIMENTS THEREOF

The illustrations shown in FIGS. 1-13 and 17-19 are of writing instrument holder devices

manufactured hand specific, in this case, for the
right hand. the preferred construction material is
of lightweight semi-rigid plastic, foam, rubber, or
composite material exhibiting qualities such as
resilience, tear resistance, ability to compress and
conform to a variety of instruments of varying
shapes inserted into the instrument holder path #1,
and have the ability to decompress or spring back to
its original shape after repeated uses. The
material may be porous to allow for long periods of
use without causing finger or hand sweating. Non-
porous materials may also be advantageous, because
they permit either wet or dry sterilization, and
offer greater stain resistance than do porous
materials. In addition, the materials should have
a tendency to conform, or give slightly under the
individual style of applying pressure to, in effect,
mold to that person's style of use and their
physical finger/hand characteristics. Weight of the
device should be such that it is comfortable to hold
for extended periods of time, and is not a negative
comfort factor in the writing process. The size of
the writing instrument holder should be such that it
fits into the palm of the hand easily, and is large
enough to accept all fingers.

In Fig. 1, a right hand unit is shown.
For greatest utility, offering finger control on one
side or the other, the unit must be manufactured
hand specific, left or right, but not precluding a
double sided unit. All figures shown are for a
right hand device. Here the right side view of Fig.
1 will serve to clarify the reason for hand specific
design. Starting from the top palm rest #6 to the
bottom finger shelf rest #14, there is a decided
twist to the right in a spiral staircase-like form.
As shown in Fig. 1A, when the palm of the hand is

placed over the palm rest #6, the fingers of the right hand will conform or fall naturally into this spiral staircase pattern. Merely grasping or draping fingers, usable or non-usable fingers, over the form will automatically position them on the device for either resting/holding and/or for downward pressure use and control. Fig. 1 shows a standard angle of use. The instrument core 1 is designed to accept a variety of small diameter, relatively smooth instruments ranging from circular to square to flat or to compound shapes, through a combination of the material's resiliency and its ability to conform to varying surfaces. Seen clearly in the top view Fig. 3, the core consists of a small bore hole which expands to accept a round instrument, and two flat cross slits through the length of the instrument which expand to accept flat to square instruments. The bore hole and cross slit width dimensions may vary with the resilience of the material used. The preformed pathways enable the material to expand and conform more easily to the shape of the instrument without straining or tearing. As shown in Fig. 1, the instrument is inserted into the core by pushing the instrument into either the top or bottom of the device which is clearly marked, until the desired length of instrument tip 4 is reached.

Using this position as an example shown in 1A for writing, the hand is draped over the palm rest. The fingers are unbent or bent slightly to conform to the device are positioned on the upper finger shelf 8 and lower finger shelf rest 14, with the option of placing the small finger also or rest 14 if desired. Depending on the mobility and use of the fingers, the vertical grasp portion 10 may be

held for further control. In the top view Fig. 3 the instrument core slit marking 1 can be seen, the oval-shaped palm rest 6 is offset to the right with the finger shelf rests 8 and 14 directly under the palm rest. A normal hand position is illustrated in Fig. 3A with the fingers on the upper and lower shelves. Depending on the dexterity of the fingers and the need to support them, rotating the device slightly counter clockwise toward the straighter side allows the fingers to be supported in a straight unbent position; rotating the device clockwise, the fingers may encircle and grip the device in an open handed grasp.

A front view of the device is shown in Fig. 2. Here the oval-shaped palm rest is seen to be offset in the direction for use by a right handed person. The fingers shelves 8 and 14 are spiraled to the right hand, and they are bevelled or sloped downward allowing finger pressure, created naturally by placement of the fingers on the platforms to act as a counterbalance to the palm pressure adding more control in the writing or instrument handling process.

The left-hand view shown in Fig. 4 exposes the underside curvature 12 of the oval-shaped palm rest 6. This area is designated as the upper bevelled detente and serves as an upper hand stop limit keeping the hand from slipping upward when used as illustrated in Fig. 4A, the thumb is shown under the palm rest, finger tips exert pressure at rests 8 and 14, while the upper detente 12 and back 18, provide counterbalance and control.

In an example of use where deformities may cause clenched or tightened fingers not able to close on a writing instrument, or a hand set in a cast with limited use of fingers, either of which

might allow only the use of the "v" between the thumb an index finger but not the palm of the hand, the device may be sued as in Fig. 4B with the thumb joint low on the left side of the device. The pressure pushing inward naturally forces the device into the "V" 15 of the hand between finger joints. As this occurs, the webbing between fingers conforms to the concave side surface 16, Fig. 5, and further secures the device adding control of the writing instrument. The inner curve of the "V" and the inner joint of the index finger follows the concave contour, and in combination with the upper detente 12, the device is cradled securely without additional controls/fingers needed.

In an almost identical situation, with the fingers clenched, or with the fingers in an open position but with little gripping ability, and where the palm of the hand is usable and desirable, Fig. 6 shows that the writing instrument holder may be held reversed, upside down with the palm rest 6 in the downward position. The writing instrument 2 to 4 is removed and reversed also. The object here again is to grasp the device in the "V" or webbing of the hand between finger joints. In this configuration the aft underside of 6 becomes the palm rest surface and is now a larger circumference object easier to grasp and is another method of control. The concave side 16 becomes an aid in guiding and nesting the holder between the webbing or "V" of the hand. Control of the device in this position is accomplished by grasping of a larger object the palm rest 6, which might be desirable for those persons with limited finger joint mobility and using the "V" between finger joints in grasping the concave surface 16 and using downward pressure on the palm rest.

Because of the ergonomic simplicity inherent in the design numerous combinations with variations of pressure control and push-pull manipulation are possible with the multiple planes and control surfaces provided to allow for maximum flexibility for individual need.

Fig. 7 through Fig. 10 show a second exemplary embodiment of the invention. The embodiment of Fig. 7 is formed of a suitable material as described above with reference to the embodiment of Fig. 1, and is similar in overall size. The embodiment of Fig. 7 has more round contours and no sharp edges. As described below, the additional round contours allow the user to develop a more personalized method of grasping the device.

Although body 100 shown in Fig. 7 is hand specific for a right handed person, it is understood that a left hand version is formed by constructing a body which is the mirror image of body 100. All references to the right side and left side of body 100 are reversed for the left hand model. also note that the left and right directions are defined so that the left side 134 of body 100 appears on the left in Fig. 9 and on the right in Fig. 7. The right side 136 of body 100 appears on the right side in Fig. 9 and on the left side in Fig. 7.

The device is formed as a single body 100 having a top portion 106, a bottom portion 120 and a bore 102 (as shown in Fig. 10) extending from the top 106 to the bottom portion 120. The bore 102 is adapted to receive an instrument. The bore is generally square in cross section with each side approximately 0.75 centimeters long. At each corner of the square bore 102 there is a slot 166 approximately 0.15 centimeters. At the top portion

106 of the body 100, the size of bore 102 is reduced to approximately 0.60 centimeters on each side to snugly grip a variety of hand held instruments. The two slots through the length of the instrument expand to accept instruments ranging in shape from flat to square and round. The bore hold and slot width dimensions may vary in accordance with the resilience of the material used. The slots enable the material to expand and conform more easily to the shape of the instrument without straining or tearing. Other cross sections may also be used for bore 102. For example, bore 102 may be round, and may have a saw-toothed cross section.

Body 100 has three portions: an ovate top portion 106, a bottom portion 120 having a lower finder shelf 114, and an upper finger shelf 108 between top portion 106 and lower finger shelf 114.

As is shown in Fig. 7 and Fig. 8, lower finger shelf 114 extends radially and downwardly from the bottom portion 120 of body 100, forming a lower finger shelf upper surface 146. Although many different parts of the hand may comfortably rest on lower finger shelf upper surface 146, surface 146 is sized to receive the dorsal surface of the terminal phalanx (the end section) of the middle finger of a user's hand. This hand position is shown in Fig. 7a. The curvature of surface 146 is gentle enough to allow the finger to rest on surface 146 without squeezing the finger. Further more, surface 146 does not precisely match the contour of the terminal phalanx, so that other hand surfaces may rest on lower finger shelf. In particular, the joint between the middle phalanx and the terminal phalanx of the middle finger may be comfortably placed in surface 146. As the middle finger rests on surface 146, the weight of the hand applied through the

middle finger provides sufficient pressure for writing and drawing.

5 The lower finger shelf upper surface 146 may extend from body 100 approximately 1.8 centimeters from inner edge 128 of surface 146 to outer edge 129 of surface 146 (the inner edge 128 is the locus of points at which the relatively flat surface 146 and the saddle shaped front surface 122 meet). although this dimension may be varied, 10 surface 146 should extend from its inner edge 128 at the front surface 122 of body 100 by a distance sufficient to extend from the lateral surface of a user's middle finger to the median of the dorsal surface of the user's middle finger. This ensures 15 that the dorsal surface of the user's middle finger rests on surface 146 without slipping off.

Surface 146 wraps around the right side 136 of body 100. Thus, with the hand grasping body 100 in an alternate position (similar to the hand position shown in Fig. 1a), surface 146 supports the lateral surface of the fourth finger. a user may also choose to rest the lateral surface of the fifth finger on surface 146 (hand position not shown). Or if body 100 is held upside down (using the hand position shown in Fig. 6), surface 146 rests on the lateral surface of the index finger. 20 25

Body 100 has a front surface 122 in the form of a saddle between finger shelf 114 and top portion 106. (Mathematically, a saddle is formed in a surface whose partial derivatives at a point are zero with respect to two orthogonal axes. The partial derivative is elsewhere positive with respect to the direction of the first axis; and the partial derivative is elsewhere negative with respect to the direction of the second axis). Front surface 122 merges with finger shelf upper surface 30 35

146 at the inner edge 128 of surface 146. Front surface 128 is sized to receive the lateral surface of the terminal phalanx of the middle finger when the dorsal surface of the terminal phalanx rests on surface 146 (as shown in Fig. 7a). The saddle shape of front surface 122 provides a comfortable gripping surface that assists in lifting body 100 (and the attached hand held instrument).

Advantageously, the size of front surface 122 is also useful for receiving the anterior surface of the fourth finger if the lateral surface of the fourth finger rests on surface 146 (similar to the hand position shown in Fig. 1a). Front surface 122 also receives the anterior surface of the fifth finger, if the lateral surface of the fifth finger rests on surface 146 (position not shown). Or, if body 100 is held upside down with the hand in the position shown in Fig. 6, the anterior surface of the index finger wraps around front surface 122.

The bottom surface 150 of lower finger shelf 114 may be round and generally convex, with a radius of curvature, of approximately 0.6 to 0.7 centimeters. Bottom surface 150 of lower finger shelf 114 extends to the bottom surface 120 of body 100, which may be flat and elliptical in shape. Using round surface 150, a user may rest body 100 on a surface at a variety of angles, or grasp the bottom surface 150 with the inside of the palm. A variation of this embodiment of the invention (not shown) includes a substantially flat lower finger shelf bottom surface 150, forming the bottom surface of body 100.

The middle portion of body 100 forms upper finger shelf 108. Upper finger shelf 108 has an upper surface 152, a vertical surface 110, and a

back surface 118. The upper surface 152 of upper finger shelf 108 has an outer edge 130, formed at the intersection of upper surface 152 and vertical surface 110.

5 As shown in Fig. 7, the left side 134 (note that left side 134 appears on the left in Fig. 9 and on the right in Fig. 7) of upper surface 152 is closer to the top portion 106 of body 100 than is the right side 136 (note that right side 136 appears on the right side in Fig. 9 and on the left side in Fig. 7). Surface 152 extends upwardly towards the left side 134. When body 100 is held in the manner shown in Fig. 7a, surface 152 provides support for the anterior surface of the proximal phalanx of the index finger.

10 Vertical surface 110 is generally convex in shape, and has a relatively large radius of curvature which may be approximately 5.0 centimeters. Vertical surface 110 extends between front surface 1222 and the outer edge 130 of the upper surface 152 of upper finger shelf 108. The bottom of vertical surface 110 merges into saddle shaped front surface 122. Thus vertical surface 110 extends outwardly from front surface 122 to outer edge 130 of upper surface 152 of upper finger shelf 108.

15 Vertical surface 110 is adapted to receive the anterior surfaces of the middle finger and fourth finger (proximal, middle and terminal phalanges) when body 100 is held in a position similar to the hand position shown in Fig. 1a. Vertical surface 110 also is adapted to receive the anterior surfaces of the index finger and middle finger when body 100 is held upside down, in a position similar to the hand position shown in Fig. 6.

20 Convex vertical surface 110 wraps around the right side 136 of body 100. On the right side 136,

vertical surface 110 extends from upper finger shelf upper surface 152 to lower finger shelf upper surface 146. At its right side 136, vertical surface 110 extends outwardly from the portion of surface 122 which wraps around the right side 136 of body 100, to outer edge 130 of upper surface 152 of upper finger shelf 108.

As shown in Fig. 8 and Fig. 9, the back surface 118 of the middle portion of body 100 is generally convex on the middle portion of body 100. There is a concave depression 116 at the bottom of back surface 118, where the middle and bottom portions of body 100 meet. Depression 116 of back surface 118 is adapted to receive the anterior side of the first finger (the thumb) of the hand, when body 100 is held in the position shown in Fig. 7a. Depending on the user's preferred hand position, depression 116 may receive the proximal phalanx of the first finger, the terminal phalanx, or the joint therebetween.

Referring now to Fig. 9, the back surface 118 of body 100 is shown. On the left side 134 of body 100 is a concave depression 138. Depression 138 is adapted to receive the anterior side of the terminal phalanx of the index finger of the hand when body 100 is held in the position shown in Fig. 7a.

As shown in Fig. 7, Fig. 8 and Fig. 9, the top portion 106 of body 100 is an ovate or egg-shaped portion 106 located above upper finger shelf 108. Ovate top portion 106 forms a palm rest similar to the palm rest 6 shown in the embodiment of Fig. 1. The surface of ovate portion 106 is generally convex. The smaller end 154 of ovate portion 106 is at the front of body 100. The larger end 156 of ovate portion 106 is at the back of body 100. Ovate portion 106 has a longitudinal axis 158 (shown in Fig. 10), which extends from smaller end 154 to larger end 156.

5 The main difference between palm rest 6
(shown in Fig. 1) and ovate top portion 106 is that
ovate portion 106 has at its bottom smoothly curved
surfaces which merge seamlessly with the contours of
upper finger shelf 108. In particular, the upper
surface 152 of upper finger shelf 108 has an inner
surface 140 which curves upwardly to join ovate
portion 106. At the front of body 100, inner surface
140 is in the form of a saddle, similar to the shape
10 of front surface 122. In surface 140 wraps around the
right side 136 and the left side 134 of body 100. As
shown in Fig. 7 and Fig. 9, the right and left sides
134 and 136 each curve upwardly to joint and merge
with ovate portion 106. Ovate portion 106 has a
curved undersurface 142 which merges with back surface
118 of body 100.

15 Convex back surface 156 of ovate portion 106
extends to meet undersurface 142 and to form a detente
112 between convex back surface 156 of said ovate
portion and underside 142. While body 100 is held in
20 the "V" between the thumb and index finger (similar to
the hand position shown in Fig. 4b), detente 112
prevents body 100 from slipping out of the hand during
use.

25 Fig. 10 shows the top portion 106 of body
100. Body 100 is volute, similar to the embodiment
shown in Fig. 1. As shown in Fig. 10, ovate portion
106, upper finger shelf 108 and lower finger shelf 114
form a spiral when viewed from above. As shown in
30 Fig. 7, upper surfaces 152 and 146 of respective upper
finger shelf 108 and lower finger shelf 114 follow a
helical path around the periphery of body 100. bore
102 has a bore axis 160. Longitudinal axis 158 of
ovate portion 106 is substantially normal to bore axis
35 160. Upper finger shelf 108 is offset by a first
angle 162 from longitudinal axis 158. Lower finger

shelf 114 is offset by a second angle 164 from longitudinal axis 158. Second angle 164 is greater than first angle 162.

5 The embodiment of the invention shown in Fig. 7 through Fig. 10 may be grasped in any of the positions illustrated and discussed above with respect to Fig. 1 through Fig. 6. further more, the added contours in body 100 provide the user with a greater range of possible hand and finger positions. The
10 potential for each user to select an individual position best suited to his or her hand shape, physiological condition and intended application is enhanced.

15 For example, Fig. 7a, 8a and 9a shown a hand draped around body 100 in a novel position. Referring to Fig. 7a, the index finger is draped over upper finger shelf 108, so that the anterior surface 172 of the proximal phalanx of the index finger 176 rests on surface 152 of upper finger shelf 108. The anterior
20 surface 174 of the middle phalanx and the anterior surface 178 of the terminal phalanx of the index finger 176 rest on the left side 134 of body 100. Referring now to Fig. 7a and Fig. 9a, the anterior surface 178 of the terminal phalanx of index finger
25 176 is received by concave depression 138 o the left side 134. As shown in Fig. 8a, the dorsal surface 170 of the terminal phalanx of the middle finger 168 is received by surface 146 of lower finger shelf 114. As shown in Fig. 9a, the anterior surface of the first
30 finger (thumb) 180 wraps around the back surface 118 and is received by the concave depression 116 shown in Fig. 9. This hand position is particularly advantageous for individuals with the physical infirmities discussed above as well as carpal tunnel
35 syndrome, and for those who may not suffer from any handicap or physical infirmity, but who tend to

develop writer's cramp. These individuals may hold a pen or pencil for longer periods with reduced pain in this manner.

5 It is understood by those skilled in the art that the embodiment of the invention shown in Fig. 7 through Fig. 10 may be customized for users who may not require all of the gripping surfaces of body 100. Fig. 11a shows two planes 182 and 184 passing through
10 body 100. Individuals who only intend to hold the device in the position shown in Fig. 7a, Fig. 8a and Fig. 9a, do not use the surfaces of body 100 above plane 182, or the surfaces below plane 184. The same is true for individuals who only intend to hold the device using the "V" between two of the fingers.

15 Fig. 11 through Fig. 13 show a further exemplary embodiment of the invention. body 200 is similar to body 100 shown in Fig. 11a, with the surfaces above plane 182 and the surfaces below plane 184 removed. For convenience, features which are the same in both body 100 (Fig. 7) and body 200 (Fig. 11)
20 have reference numerals with the same last two digits; only the most significant digit of the reference numeral is changed from 1 to 2.

25 The materials used in body 200 are the same as those used in body 100. body 200 is particularly suitable for individuals who wish to hold the instrument gripping device in the hand position shown in Fig. 7a, Fig. 8a and Fig. 9a. Upper surface 252 of upper finger shelf 208 is substantially flat, and may
30 be inclined slightly to be higher on the left side of body 200 than on the right side. The increased area of upper surface 252 (relative to the upper surface 152 in the embodiment of Fig. 7) provides more room to support the anterior surface of the proximal phalanx
35 of the index finger, as well as a portion of the palm. The flat bottom surface 220 allows placement of the

hand closer to the writing surface than is possible when body 100 is used.

The remaining surface features of body 200 are the same as described above with reference to Fig. 7, Fig. 8 and Fig. 9. In particular, lower finger shelf 214, inner edge 228, front surface 222, concave depression 238, concave vertical surface 210, back 218 concave depression 216, underside 242, and outer edge 230 are all similar to respective features 114, 128, 122, 138, 110, 118, 116, 142 and 130 as shown in Fig. 7 through Fig. 9. This embodiment of the invention may be more attractive to some users because, even though the features common to bodies 100 and 200 are the same size, the overall length of body 200 (approximately 5 centimeters) is about half the overall length of body 100 (approximately 10 centimeters). This makes body 200 easy to transport in a pocket or purse.

Body 200 may also be used effectively in a number of other hand gripping positions, such as in the "V" between a pair of fingers. Just as the flattened bottom surface 220 allows the hand to be positioned closer to the writing surface than when body 100 is used, if body 200 is inverted, the flat upper surface 252 allows the hand to be placed closer to the writing surface.

Fig. 14 through Fig. 16 show a further exemplary embodiment of the invention. Unlike the embodiments of Fig. 1, Fig. 7 and Fig. 11, body 300, as shown in Fig. 14 through Fig. 16 is not hand specific. As shown in Fig. 16, there is an axis of symmetry 392. Body 300 may be more desirable for use by ambidextrous individuals, and by those who prefer an even more compact size than body 200 shown in Fig. 11. body 300 is shorter, measuring about 3.5 centimeters from bottom surface 320 to top surface

386. Nonetheless, body 300 still features important aspects of the invention, as explained below.

Referring to FIGS. 14 and 15a, body 300 has a top portion 386, a bottom portion 320 and a bore 302 extending from top portion 386 to bottom portion 320. Bore 302 is similar to bore 102 discussed above with reference to Fig. 7, and is adapted to receive an instrument.

Body 300 has a finger shelf 314 extending radially outwardly and downwardly from bottom portion 320 of body 300, forming a finger shelf upper surface 346 sized to receive the dorsal surface 370 of the terminal phalanx of the middle finger 368 of the hand.

Body 300 has a front surface 322 in the form of a saddle between finger shelf 314 and top portion 386, with front surface 322 extending to and merging with finger shelf upper surface 346. Front surface 322 is sized to receive a lateral surface of the terminal phalanx of the middle finger 368.

Finger shelf upper surface 346 extends from front surface 322 of body 300 by a distance sufficient to extend from the lateral surface to the median of the dorsal surface 370 of the terminal phalanx. In the exemplary embodiment, finger shelf 346 is extended even further, sufficient to extend out by the full width of the middle finger, approximately 1.4 to 1.5 centimeters from the inner edge 328 of surface 346. The extended length provides extra support for the middle finger, and allows the hand to transmit more force with the middle finger easily.

Finger shelf 314 extends approximately three quarters of the way around body 300, as shown in Fig. 16. Again, this allows use of a single device by either hand, still providing a surface 346 to receive the dorsal surface of the middle finger terminal phalanx.

Unlike the embodiments of Fig. 1, Fig. 7 and Fig. 11, the saddle shaped front surface 322 of body 300 wraps around body 300, merging with a back saddle surface 388. A horizontal cross section (not shown), perpendicular to bore 302, would be substantially circular. The anterior surface 394 of the terminal phalanx of the first finger is received by the back saddle surface 388. The anterior surface of the terminal phalanx of the index finger (not shown) is received by the saddle shaped surface on the left or right side of body 300. The symmetrical aspect of saddle shaped front surface 322 makes body 300 useful by right handed, left handed and ambidextrous individuals. There are no concave depressions unique to the left, right, front or back sides of body 300.

Another difference between body 300 and the embodiments of Fig. 1, Fig. 7 and Fig. 11 is that body 300 does not include the upper finger shelf. The anterior surface of the index finger does not rest on the top portion 386 of body 300. body 300 is gripped only the terminal phalanges of the first, second and third fingers. Unlike the conventional grip of an instrument (i.e., the grip used for an instrument without a holder) in which the lateral surface of the middle finger is used to hold the instrument and apply pressure, body 300 provides means to apply pressure to the instrument using the dorsal surface of the middle finger. this grip is common with the other embodiments of the invention described herein. The top portion 386 of body 300 has a greater diameter than the saddle shaped surfaces 322, 388, 395 and 397. The larger top portion assists in preventing body 300 from slipping out of the user's hand.

Fig. 16a shows a different hand position which may be used to grip body 300. In this position, body 300 is rotated about bore 302 by an angle of about 90 degrees from the position shown in Fig. 15a. This

position provides a slightly different writing angle, and allows the index finger to rest on the extended portion of finger shelf 314. The dorsal surface of the terminal phalanx of the middle finger rests on the portion of finger shelf upper surface 346 on the side 395 of body 300. It will be understood by one skilled in the art that body 300 may be rotated to any position in the 90 degree range between that shown in Fig. 15a and that shown in Fig. 16a to suit the individual user's style.

Fig. 17 through Fig. 20 shown another embodiment of the invention. body 400, shown in Fig. 17, is similar to the embodiment of Fig. 14, except that body 400 is hand specific, and is made for right handed individuals. The overall size of body 400 is similar to that of the embodiment of Fig. 14. Like body 300 (shown in Fig. 14) body 400 has a top portion 486 which has a greater diameter than the middle portion formed by surfaces 422, 488, 495 and 497. top portion 486 assists in preventing body 400 from slipping downward or dropping. It is understood that reversal of all surface locations results in a left hand model. although the right and left handed models are geared towards typical right and left handed users, respectively, an individual right handed user may prefer the left handed mode, and a left handed user may prefer the right handed model.

Body 400 has a top portion 486, a bottom portion 420 and a bore 402 extending from top portion 486 to bottom portion 420. bore 402 is similar to bore 102 discussed above with reference to Fig. 7, and is adapted to receive an instrument.

Body 400 has a finger shelf 414 extending radially and downwardly from bottom portion 420 of body 400m, forming a finger shelf upper surface 446 sized to receive the dorsal surface of the terminal phalanx of the middle finger of the hand. This hand position is similar to the hand position shown in Fig. 15a.

Body 400 has a front surface 422 in the form of a saddle between finger shelf 414 and top portion 486, with front surface 322 extending to, and merging with, finger shelf upper surface 446. Front surface 422 is sized to receive a lateral surface of the terminal phalanx of the middle finger 468.

Finger shelf upper surface 446 extends from front surface 422 of body 400 by a distance sufficient to extend from the lateral surface to the median of the dorsal surface of the terminal phalanx. Like finger shelf 314 shown in Fig. 15, finger shelf 414 is extended even further, sufficient to extend out by the full width of the middle finger, approximately 1.4 to 1.5 centimeters from the inner edge 428 of surface 446. the extended length of finger shelf 414 provides extra support for the middle finger, and allows the hand to transmit more force with the middle finger easily.

As shown in Fig. 18, a concave depression 496 is in the center of finger shelf upper surface 446. When the dorsal surface of the terminal phalanx of the middle finger is received by surface 446, the joint between the middle phalanx and the terminal phalanx is received by concave depression 496, enhancing comfort and increasing the gripping surface. It is understood by those skilled in the art that the position of the concave depression 496 may be shifted slightly towards the left or right of the center of surface 446. In particular, moving depression 496 towards left side 497 provides a larger area on surface 446 on which the terminal phalanx of the middle finger rests while the joint is received by depression 496.

Body 400 has no axis of symmetry. Between the finger shelf 414 and the top portion 486 are front saddle surface 422, side saddle surfaces 495 and 497, and a back saddle surface 488. As shown in Fig. 17, front surface

422 is shallower than back surface 488. The shallower front surface may receive a portion of the lateral surface of the middle phalanx of the middle finger, as well as the terminal phalanx. Back surface 488 is adapted to receive the anterior surface of the terminal phalanx of the first finger.

As shown in Fig. 18, surfaces 495 and 497 differ from one another, to allow more personalized gripping positions. Side surface 497 is relatively deep, to receive the anterior surface or tip of the terminal phalanx of the index finger. Side surface 495 is shallower. The depth of the saddle shaped surface varies between right side 495 and left side 497. by rotating body 400 slightly within the hand, the user can adopt a grip which is most comfortable for him or her.

As shown in Fig. 18, bore 402 is substantially perpendicular to finger shelf surface 446, and is approximately midway between right side 495 and left side 497. a variation of the embodiment of Fig. 18 (not shown) includes a bore which is inclined towards side 499 at the top portion. The off-center bore provides a slightly different writing angle than is provided with the 90 degree angle shown in Fig. 18. the shallow right surface 495 allows placement of bore 402 closer to side 495 without causing any structurally weak zones in body 400.

As shown in Fig. 20, finger shelf 414 does not extend as far around body 400 as does finger shelf 314 shown in Fig. 16. Because body 400 is hand specific, the larger shelf angular coverage is not required.

Fig. 21 shows a further embodiment of the invention, in which gripping device 503 is pre-configures to include a hand held instrument. the gripping device 503 and the housing 501 or outer barrel of the hand held instrument are merged into a single body 500 with the gripping device. In Fig. 21, housing 501 is the barrel

of a writing instrument, which may be a pen or a pencil (e.g., mechanical pencil). Body 503 includes a finger shelf 514 with an upper surface 546 adapted to receive the dorsal surface of the terminal phalanx of the middle finger, as shown in Fig. 21a. A front surface 522 is adapted to receive the lateral surface of the middle finger. On the opposite side of housing 501 from finger shelf 514 is a back surface 588 adapted to receive the anterior surface of the terminal phalanx of the first finger. Surfaces 522, 546 and 588 may be hand specific, similar to surfaces 422, 446 and 488 shown in Fig. 17 through Fig. 20. Surfaces 522, 546 and 588 may also be non hand specific, as shown in Fig. 14 through Fig. 16. Fig. 21b is a plan view of the gripping device incorporating the writing implement. Surface 546 of the finger shelf may include a concave depression similar to the finger shelf surface 446 in the embodiment of Fig. 17.

As shown in phantom in Fig. 21, the top portion of body 500 may optionally be constructed to wrap all the way around housing 501, forming an additional surface 587 to assist in gripping body 500.

Fig. 22 shows a variation of the embodiment of Fig. 21. In Fig. 22, instrument 601 is a cutting instrument, which may be a knife (as shown) or other surgical or dental instrument. It is understood by those skilled in the art that a variety of gripping devices may be manufactured in this manner, with any one of a variety of hand held instruments integrated into the respective gripping device bodies. These instruments may include, but are not limited to eating utensils, tools, toothbrushes, and paintbrushes.

Fig. 23 shows still another embodiment of the present invention which is extremely advantageous for use by individuals having normal ability in handling and/or

gripping instruments and the like as well as those having less than normal skills and is extremely advantageous for use by persons constantly performing repetitive manual operations with instruments or the like.

5 Figs. 23 and 24-26 show another embodiment of the present invention 700 having an elongated bore 701 terminating in openings 702 and 703 at the respective upper and lower ends thereof. The bore is preferably either cylindrical or may have any other configuration, 10 the holder 700 being formed of a resilient, rubber-like material capable of undergoing some stretching in order to conform to the outer periphery of an instrument having a non-circular shape.

15 Fig. 23 shows an instrument I which may be a pencil, pen, handle of a cutting knife having a cutting blade (one such hand held cutting instrument being identified by the trademark XACTO).

20 An instrument I is pushed through bore 701 and can be seen to be of a length which is substantially greater than the length of device 700. Device 700 is positioned at any location along the length of instrument I depending only upon the needs of the user which is based principally upon the comfort and ease of use and holding of the operator. The top end of device 700 has 25 a generally annular shape periphery except for a truncated portion which comprises the top end of a gripping surface 703 which extends downwardly from the top end adjacent opening 702 and curves slightly inwardly in the region 704 and thereafter curves outwardly over 30 the region 705 to form a somewhat J-shaped or "ski-slope" configuration when viewed as a side elevation. The lower end forms a curved edge or vertex 706 of the gripping surface which extends outwardly from the bore 701 by a distance greater than the upper end 707.

The upper region of the gripping surface 703 extending from top 707 to about the intermediate portion thereof is substantially flat and parallel to axis A while the remaining surface from the intermediate portion to the bottom edge 706 has a substantially curved concave surface gradually extending downwardly and away from axis A.

The device 700 tapers gradually downwardly from the top toward a narrower intermediate or "waist" region 708 and then tapers outwardly from the intermediate region toward the bottom of the device 700 which curves radially inwardly to merge with the perimeter of bottom opening 703. Device 700, excluding the gripping surface 703, has a generally "hour glass" shape comprised of top and bottom portions which gradually taper radially inwardly to define the waist portion.

The intermediate region on the sides adjacent gripping surface 703 and the portion thereof between said sides and opposite said gripping portion 703 is of reduced diameter, the taper being a gradual curvature. The intermediate surface region thus has a curved concave contour. The surface 709 opposite the gripping surface 703 tapers inwardly a slightly greater amount than the side surfaces 708a, 708b shown in Fig. 25.

Some of the possible arrangements which may be utilized to grip device 700 are shown in Figs. 23A-23D.

Fig. 23A shows one manner in which device 700 may be gripped by one finger and a thumb of a right hand. More specifically, the interior surface 720 of the terminal phalanx of thumb 721 presses on the lower concave surface portion of gripping surface 703 while the anterior surface 722 of the terminal phalanx of index finger 723 rests upon the surface area 709 of reduced diameter. The forces exerted by thumb 721 and index finger 723 in the direction extending radially inwardly

0344B44.043097
5 toward instrument I need only be minimal and in fact is
substantially negligible. The forces exerted by index
finger 723 and thumb 721 and principally thumb 721 in a
direction parallel to the longitudinal axis A of
instrument I is significantly greater than the force
needed to grip the device 700 and hence instrument I.
This is made possible due to the fact that the concave
curvature of the rear surface portion 709 cooperates with
the gripping surface 703 to prevent the device 700 and
hence instrument I from moving either upwardly or
downwardly. The operator may therefore concentrate
principally upon the application of force necessary to
press the instrument upon a sheet of paper or to perform
some other operation such as cutting, scraping, pushing,
pulling or the like.

10
15 Fig. 23b shows the device 700 holding
instrument I and being gripped by the thumb 724 and index
finger 725 of an operator's left-hand. More
specifically, the anterior surface 726 of the terminal
phalanx of index finger 725 rests along nearly the entire
gripping surface 703 from the top thereof to nearly the
bottom edge 706, the gripping surface having a contour
which substantially conforms to the shape of the anterior
surface of the index finger resting thereon.

20
25 The anterior surface 727 of the terminal
phalanx of thumb 724 engages the intermediate portion 709
of the back surface and the intermediate portion 708b of
the right-hand surface. Similar to Fig. 23A, the force
exerted radially inwardly by thumb 724 and finger 725 is
minimal and substantially insignificant, due to the
unique contour of device 700. In contrast, the downward
force, i.e. the force exerted parallel to the
longitudinal axis A of instrument I is significantly
greater and is principally a function of the nature of
the instrument being manipulated and the operation being

30
35

performed. For example, a writing instrument such as a pen (either a ball point or a nib-type pen) or pencil requires only a light downward force whereas a cutting instrument, an artist's or leather worker's tool or a dental instrument such as a dental pick may require a greater (pushing or pulling) force.

Device 700 is extremely advantageous for use in instances where repeated operations over a long period of time would otherwise cause significant strain and/or fatigue experienced due to use of the normal forces required to press a pen or pencil, for example, between the thumb and index and third fingers. Alternatively, persons lacking the ability to provide such normal pressing forces may nevertheless have the ability to hold the instrument while exerting an insignificant if not imperceptible pressing force.

Fig. 23C shows still another arrangement in which device 700 is gripped by the thumb 721, index finger 728 and third or middle finger 729 of an operator's right hand. More specifically, the dorsal surface of the terminal phalanx 730 engages gripping surface 703. The interior surface and a portion of the side surface between the interior and dorsal surface of the terminal phalanx 720 of thumb 721 engages the rear intermediate surface 709 (see Fig. 25) and may also rest somewhat on the surface portion 708b. Middle finger 728 need not even engage the device 700 and, merely as a matter of an operator holding the fingers in a comfortable position, finger 28 may touch only the anterior surface of the terminal phalanx of thumb 721 or alternatively may touch upon the regions 708a of device 700 or may touch upon portions of the thumb 721 and device 700 mentioned immediately hereinabove.

Again, the pressing force required to be exerted upon device 700 by the fingers and thumb in the

inward radial direction is substantially insignificant for the reasons set forth hereinabove while, in contrast, the downward force exerted in the direction parallel to the longitudinal axis of instrument I is significantly greater than any inward radial force exerted on the instrument and is a function of the nature of the operation being performed, as was described hereinabove. In addition, the principal downward force may be exerted by and is preferably exerted by the middle finger 729.

As a modification of the arrangement shown in Fig. 23C, the knuckle portion of the finger 729 between the terminal phalanx and the intermediate phalanx may engage and rest upon the gripping surface 703 and more specifically the lower, concave, curved region 705 (see Fig. 23). Alternatively, both a portion of the dorsal surface of the terminal phalanx finger 729 and the aforementioned knuckle may engage and rest upon gripping surface 703.

Fig. 23D shows still another gripping arrangement in which the index and middle or third fingers 725 and 731 and the thumb 724 of a left-hand grips device 700. More specifically, the dorsal surface of the terminal phalanx of the middle finger 731 rests upon the lower surface portion 705 of gripping surface 703. The anterior surface of the terminal phalanx of thumb 724 rests upon surface portion 709. The anterior surface of the terminal phalanx of index finger 725 rests upon surface portion 708b. The forces required to manipulate instrument I may be obtained principally from middle finger 731 and thumb 724 and the positioning of the index finger 705 may be more a matter of placement in the manner shown in Fig. 23D for purposes of comfort more so than for purposes of urging instrument I toward (or away from) a surface being worked upon. The anterior surface portion of index finger 725 may rest exclusively

upon an engaging surface of thumb 724 or exclusively upon surface 708b of device 700 or may rest upon partial surfaces of both the device 700 and thumb 724. The principal downward forcing exerted upon instrument I may be derived from the middle finger 731. As an alternative to the arrangement shown in Fig. 23D, the knuckle portion of finger 731 located between the terminal phalanx and the middle phalanx may rest upon the lower portion of 705 of gripping surface 703. As a further alternative, the dorsal surface of the middle phalanx of middle finger 731 may rest upon surface portion 705. Any of these alternative holding arrangements may be utilized with equal success in holding instrument I for the performance of a given operation. In addition, an operator may shift from one gripping arrangement to another as a means for reducing discomfort, strain and the like. A number of the gripping arrangements described for use with the embodiments of FIGS. 1-22 may also be used.

Fig. 27 shows an alternative embodiment 700' of the device shown, for example, in Fig. 23 wherein opposite end portions 700a', 700b' are substantially identical in design and function to the device 700 shown in Fig. 23 and wherein the portions 700a' and 700b' are joined by at least and preferably two joining strips 700c', 700d'. This embodiment is extremely useful in conjunction with dental and other instruments wherein different types of implements are provided at opposite ends of a common handle H having instrument ends I' and I". This arrangement enables an operator to switch the use of one instrument I' to the other instrument I" without removing and reversing a single device 700. As further alternatives, connector strips 700c' and 700d' may be replaced by a continuous, cylindrical arrangement or alternatively may be eliminated altogether, thereby

effectively providing two independent devices 700a' and 700b'.

Fig. 28 shows still another alternative embodiment 800 of the present invention comprised of a barrel 802, cap 804 and integrated holding section 806. A pen (or pencil) tip 808 extends from the lower end of gripping portion 806.

Gripping portion 806 is provided with a substantially J-shaped indented finger guide or groove 810, which extends substantially diagonally downward and inward having a concave portion 810a, which merges into a lower fixed saddle 810b and terminates in a pressure edge 810c. The remaining portion 812 of the gripping section 806 has a waist region 812a of reduced diameter providing a generally hour-glass-shaped contour. Upper portion 812b is of a substantially constant diameter with a lower end of barrel 802 so that the external surfaces of these members are substantially flush, and tapering gradually along a smooth curvature to the waist region 812a of reduced diameter and thereafter tapering outwardly to region 812c. The remaining portion of gripping section 806 tapers to a substantially narrow opening 814 from which the pen (or pencil) end tip extends.

The sides 816, 818 (Fig. 30) of gripping section 806, which are arranged between the J-shaped finger guide 810 and the rear surface portion 812 are generally straight, measured in the longitudinal direction and have a substantially constant convex curvature measured in a plane perpendicular to the longitudinal axis of the instrument.

The contours of the gripping section 806 substantially resemble those of the gripping member 700 shown in Figs. 23-27. The major distinction being that

the gripping section 806 forms an integral part of the instrument 800.

Incidentally, although the instrument 800, shown in Fig. 28 is, the preferred embodiment, preferably either a pen or pencil, the pen or pencil may be replaced or incorporate a cutting, probing (i.e. electric heating or sensing device) or scoring member, if desired without departing from the scope or spirit of the invention. The opening at 814 may be sized and shaped to receive the desired operating instrument.

FIGS. 28A-28C show three possible ways in which the instrument may be held, it being understood that a variety of other ways may be utilized to hold the instrument depending upon the needs (and/or ingenuity) of the user.

Fig. 28A shows one such arrangement. The right-hand of the user is holding instrument 800 such that the anterior portion IFa of index finger IF rests in the J-shaped surface 810 so that the tip IFt of the finger rests upon the saddle portion 810b and tip of thumb T rests in the waist region 812a while the middle finger MF has the side thereof resting upon the side 816 of instrument 800 (see Fig. 30). Only light pressure need be exerted in a generally inwardly radial direction by the thumb T and middle finger MF. Downward pressure is exerted by the tip IFt of index finger IF on the saddle portion 810b for writing, for example.

In the arrangement shown in Figure 28B, instrument 800 is shown being held by thumb T and index finger IF of the right-hand of user. The side of the thumb T rests against the J-shaped surface 810a (see Fig. 28) while the tip portion of the thumb rests upon saddle portion 810b. The tip of index finger IF is shown resting just below waist region 812a (see Fig. 28). Only light pressure need be applied by the tip of index finger

IF to hold instrument 800. Downward pressure is applied by the tip of thumb T against saddle portion 810b.

Figure 28C shows still another manner in which instrument 800 may be held. In this example, the thumb, index finger and outer knuckle of the middle finger are utilized for holding purposes. The tip of thumb T rests against waist portion 812a (see Fig. 28). The outer knuckle MFa of middle finger MF rests upon saddle portion 810b (see Fig. 28), while index finger IF has its anterior portion extending about the lower portion of barrel 802 and the upper portion of side 818 of instrument 800 (see Fig. 30).

In a manner similar to the arrangement shown in 28A and 28B, only light pressure need be applied in a generally inwardly radial direction by thumb T and index finger IF while the knuckle MFa of middle finger MF applies the downward pressure against saddle 810b of the instrument 800.

Figures 29A and 29B show details of the internal structure of instrument 800 when utilized as either a pen or pencil. A narrow, elongated tubular ink supply member 814 is arranged within instrument 800 and is offset relative to a longitudinal central axis CL. The barrel 814, which may be an ink supply barrel or a lead supply member are arranged in the off-center manner shown in Figs. 29 and 29A to balance the instrument 800 thereby offsetting the opposing or mainly diagonally downward force applied to the lower finger saddle 810b. In addition, the tip 808, which is likewise offset from center line CL, angles the instrument in use thereby orienting the finger saddle more to the finger used thereon making a more secure platform by orientation rather than increasing the size of the saddle.

The offset of tip 808 necessitates offset alignment of tubular supply member 814.

Pen cap 804 may either be force-fittingly or threadedly mounted upon the upper end of barrel 802, which may be provided with an upper end 802a of reduced diameter to telescope into the interior of 804. The engaging portions may be threaded to threadedly engage one another or may be of a tight tolerance for a good force-fit.

The interior of cap 804 has an annular recess 804a of a tapering cross-section, tapering from a wide open end to a narrow base 804a-1. This recess receives and accurately positions the upper end 814a of supply barrel 814. The provision of a circular-shaped recess assures proper retention of the upper end 814a of supply barrel 814 even in the event that the cap 804 is rotated to a different angular position each time it is replaced upon barrel 802.

Figure 29B shows a protective cover cap 816, which may be utilized to protect the instrument tip 808. The cover cap has a substantially eccentric conical shape which generally conforms to the shape of the instrument over the region from the extreme end of tip 808 to a position just slightly above the pressure edge 810c on one side thereof, and just slightly above region 812c on the opposite side of instrument 800 (see Fig. 28).

The cap 816 has an interior dimension which is close to the exterior dimension of the lower end of instrument 800 so as to provide a good force fit. Cap 816 may be provided with an internal lip 816a, which extends just slightly inwardly to provide a snap-fit with the pressure edge 810c. A pocket clip 818 has a first end thereof secured to cap 816 and the major portion thereof 818a extending over the upper portion of gripping section 806 so as to be clipped into the pocket of the user, for example.

5 The instrument 800 thus has a gripping section
which embraces all of the favorable characteristics of
the gripping member 700 shown, for example in Fig. 23,
while at the same time providing a wholly integrated
instrument, and when employed as a pen or pencil has an
off center ink/lead supply (or other internal member)
which angles the instrument when in use, for example, in
the writing process, exposing more of the pressure
applied to the finger surface. This automatic angling
10 assures that the applied force is exerted in a diagonal
direction rather than directly downward, the approximate
10-20° angle (dependent upon a user's style) exposes more
of the finger ledge and saddle. In addition, a smaller
finger saddle/lower pressure ledge may be utilized with
15 equal success. The smaller finger saddle/lower pressure
ledge provides a more balanced instrument in both
appearance and use (in appearance, without the balance
described hereinabove through the offset tip, the lower
pressure ledge 810c would have to be larger, providing
20 the pen with an awkward and unbalanced or "bottom heavy"
appearance).

Although the descriptions and illustrations
above contain numerous specifications and illustrations
for use, these should not be construed as limiting the
25 scope of the invention but as merely providing
illustrations of some of the presently preferred
embodiments of this invention.

A latitude of modification, change and
substitution is intended in the foregoing disclosure, and
30 in some instances, some features of the invention will be
employed without a corresponding use of other features.
Accordingly, it is appropriate that the appended claims
be construed broadly and in a manner consistent with the
spirit and scope of the invention herein described.

WHAT IS CLAIMED IS:

1. A device for aiding in the gripping of a hand held instrument normally held by the hand without a gripping aid, comprising:

5 a body having a top portion, a bottom portion and a bore extending from said top to said bottom portion terminating in top and bottom openings, said bore adapted to receive an instrument having a length greater than said bore,

10 said body frictionally engaging said instrument enabling the body to be adjustably positioned along a length of the instrument,

15 said body having a finger shelf extending radially and downwardly from said bottom portion of said body, forming a finger shelf upper surface sized to receive a dorsal surface of a terminal phalanx of a middle finger of a hand,

20 said body having a front surface in the form of a saddle between said finger shelf and said top portion with said front surface merging with said finger shelf upper surface, said front surface sized to receive a lateral surface of the terminal phalanx of the middle finger, and

25 said finger shelf upper surface extending from said front surface of said body by a distance sufficient to extend from said lateral surface to the median of said dorsal surface.

30 2. A device in accordance with claim 1, wherein said body further comprises a back surface in the form of a saddle, said back surface adapted to receive the anterior side of the first finger of the hand.

3. A device in accordance with claim 1, wherein said upper surface of said finger shelf is substantially flat.

5 4. A device in accordance with claim 1, wherein said finger shelf is a lower finger shelf, said device further comprising an upper finger shelf extending radially from said body having an upwardly facing upper surface sized to hold an index finger of a hand, said upper surface of said upper finger shelf being adapted to receive an anterior side of a proximal phalanx of an index finger.

10 5. A device in accordance with claim 4, wherein said upper surface of said lower finger shelf has an inner edge, said upper surface of said upper finger shelf has an outer edge, said body having:

15 a vertical surface which is convex in shape, said vertical surface located between said upper finger shelf and said lower finger shelf, said vertical surface extending outwardly from said inner edge of said upper surface of said lower finger shelf to said outer edge of said upper surface of said upper finger shelf.

20 6. A device in accordance with claim 5, wherein said front surface is located between said upper finger shelf and said lower finger shelf.

25 7. A device in accordance with claim 4, wherein said upper surface of said upper finger shelf has a left side and a right side, said finger shelf extending upwardly towards a selected one of said left side and said right side.

8. A device in accordance with claim 4, wherein said bore has an axis, and said lower finger shelf is offset from said upper finger shelf by a predetermined angle about said axis.

5 9. A device in accordance with claim 4, wherein said body further comprises a left side and a right side, and a selected one of said left and right sides has a surface in the form of a saddle, said surface of said selected side being adapted to receive the
10 anterior side of the terminal phalanx of the index finger of the hand.

10. A device in accordance with claim 9, wherein said upper surface of said upper finger shelf extends upwardly toward said selected side.

15 11. A device in accordance with claim 4, wherein said body further comprises a left side and a right side, and a selected one of said left and right sides has a surface with a concave depression, said concave depression being adapted to receive the anterior
20 side of the terminal phalanx of the index finger of the hand.

25 12. A device in accordance with claim 11, wherein said upper surface of said lower finger shelf has an inner edge, said upper surface of said upper finger shelf has an outer edge, and wherein the other one of said left and right sides has a side surface which is convex in shape, said side surface located between said upper finger shelf and said lower finger shelf, said side surface extending outwardly from said inner edge of said
30 upper surface of said lower finger shelf to said outer edge of said upper surface of said upper finger shelf.

13. A device in accordance with claim 4, wherein said upper finger shelf has a right side and a left side, said body having:

5 a back surface in the form of a saddle, and
an ovate portion located above said upper
finger shelf, wherein said upper surface of said upper
finger shelf has an inner surface which curves upwardly
to join said ovate portion, said right and left sides
10 each curving upwardly to join with said ovate portion,
said ovate portion having a curved undersurface which
merges with said back surface of said body.

14. A device in accordance with claim 13,
wherein said ovate portion has a convex back surface
which extends to meet said undersurface and to form a
15 detente between said convex back surface of said ovate
portion and said underside, thereby to prevent said
device from slipping out of the hand.

15. A device in accordance with claim 14,
wherein said bore has a bore axis, said ovate portion has
20 a longitudinal axis substantially normal to said bore
axis, said upper finger shelf is offset by a first angle
from said longitudinal axis, and said lower finger shelf
is offset by a second angle from said longitudinal axis,
said second angle being greater than said first angle.

25 16. A device in accordance with claim 1,
wherein said finger shelf has a flat bottom surface.

17. A device in accordance with claim 1,
wherein said body has a left side and a right side, and
said upper surface of said finger shelf is substantially
30 flat between said left side and said right side.

18. A device in accordance with claim 1, wherein said finger shelf has a convex bottom surface.

19. A device in accordance with claim 1, wherein said body further comprises a back surface having a depression, said back surface adapted to receive the anterior side of the first finger of the hand.

20. A device in accordance with claim 1, wherein said body includes a writing instrument.

21. A device in accordance with claim 1, wherein said body includes a cutting instrument.

22. A device in accordance with claim 1, wherein said body includes a dental pick instrument.

23. A device in accordance with claim 1, wherein said finger shelf includes on its upper surface a concave depression adapted to receive a joint between the middle and terminal phalanges of the middle finger.

24. A device in accordance with claim 1, wherein said body includes a left surface, a right surface and a back surface, each of said left, right and back surfaces in the form of a saddle, each of said left, right and back surfaces located between said finger shelf and said top portion of said body.

25. A device for aiding in the gripping of a hand held instrument normally held without need for an additional member to aid in gripping thereof, comprising:
a body having a bore adapted to frictionally grip said instrument at an adjustable position along a length of the instrument,

(Claim 25 continued)

5 said body having an upper finger shelf
extending radially from said body having an upwardly
facing upper surface sized to hold an index finger of a
hand, said upper surface of said upper finger shelf being
adapted to receive the anterior side of the proximal
phalanx of the index finger,

10 said body having a lower finger shelf extending
radially and downwardly from said body forming an upper
surface sized to hold the middle finger of the hand, said
upper surface of said lower finger shelf being adapted to
receive the dorsal surface of the terminal phalanx of the
middle finger.

15 26. In combination, an instrument and a
gripping device for aiding in the gripping of said
instrument, said instrument having a barrel portion and
an operating portion extending from an end of the
instrument opposite said barrel portion for performing an
operation, said gripping device being an integral part of
20 said instrument positioned between said barrel portion
and said operating portion, and comprising:

 first and second ends respectively adjacent to
said barrel portions and said operating portion;

25 a body of said gripping device between said
first and second ends having a shelf extending radially
outward from the opening in said first end, a surface
area of one surface of said shelf being of a size
sufficient to engage a portion of any finger of a hand
holding said device;

30 said surface being aligned transverse to a
longitudinal axis of said instrument;

 said body having a substantially annular-shaped
surface opposite said shelf which gradually reduces in

diameter from said first end toward an intermediate portion between said first and second ends and which gradually increases in diameter from said intermediate portion toward said second end to form an intermediate region of reduced diameter which is of a size sufficient to receive portions of any finger of the gripping hand whereby a force for urging said operating portion against an engaging surface is applied to said shelf in a direction substantially parallel to said longitudinal axis and is significantly greater than forces required to hold said device and which are applied in a direction substantially perpendicular to said longitudinal axis.

27. In combination, an instrument and an integral gripping device for aiding in the gripping of the instrument, said instrument having a barrel portion held by a barrel portion and an operating portion extending from an end of the instrument opposite said barrel portion for performing an operation, said gripping device being an integral part of said instrument positioned between said barrel portion and said operating portion, and comprising:

first and second ends respectively adjacent said barrel portion and said operating portion;

a body of said gripping device between said first and second ends having a generally annular shape and curving radially outwardly and then downwardly in moving from said second end to said first end and generally tapering inwardly at a portion of said one-piece body intermediate said first and second ends and gradually curving outwardly from said intermediate portion toward said second end;

a finger engaging surface extending from said second end toward said first end, said surface being aligned generally parallel to a longitudinal axis of said

instrument and gradually curving outwardly along a lower portion thereof adjacent said first end and terminating in an edge which joins a curved convex surface which forms said first end and extends radially inwardly toward the opening in said first end;

said lower curved portion having a curved convex shape defining a force applying shelf diagonally aligned with the longitudinal axis, said finger engaging surface having a contour for resting a finger of a gripping hand thereon and said shelf portion provided to urge said operating portion toward engagement with the surface by application of a force to said shelf portion by any one of a tip, lateral surface, dorsal surface or knuckle of a finger applied thereto;

said gradually tapering intermediate portion being of a size sufficient to be engaged by at least another finger of a gripping hand which by engaging said tapered portion is capable of supporting the device with only a minimum force exerted upon said device in a direction perpendicular to said longitudinal axis whereas the force acting on said shelf and applied in a direction generally parallel to said longitudinal axis is significantly greater than the force supporting said device.

28. In combination, an instrument and an integral gripping device for aiding in the gripping of said instrument, said instrument having a barrel portion and an operating portion extending from an end of the instrument opposite said barrel portion for performing an operation, said gripping device being an integral part of said instrument positioned between said barrel portion and said operating portion, and comprising:

first and second ends respectively adjacent said barrel portion and said operating portion;

(Claim 28 continued)

5 a body of said gripping device between said first and second ends having a truncated annular-shaped periphery defining a cross-section having a substantially D-shaped perimeter at said first end, a flat surface portion of the truncated periphery defining a linear portion of said D-shaped perimeter;

10 said body having an annular periphery at said second end;

15 said flat surface portion defining a gripping surface which is substantially flat over a portion of its length between said first end and said second end and which curves gradually over the remainder of its length to provide a curved convex surface portion;

20 the annular-shaped periphery of said one-piece body gradually tapering inwardly from said first end toward an intermediate portion and thereafter tapering outwards toward said second end to define a substantially hour glass shape.

25 29. The combination according to claim 28, wherein said flat portion of said gripping surface is substantially parallel to a longitudinal axis of said bore.

30 30. The combination according to claim 29, wherein the curved convex surface area curves away from said longitudinal axis.

31. The combination according to claim 28, wherein said gripping surface has a width measured transverse to said longitudinal axis which increases from said first end to said second end.

32. The combination according to claim 28, wherein said second end surrounding the opening therein has a substantially hemispheric shape.

5 33. The combination according to claim 28, wherein the gripping surface terminates in a curved arcuate edge.

10 34. The combination according to claim 28, wherein a radial distance of a perimeter of said annular periphery at said second end is at least equal to a distance of a curved portion of said D-shaped perimeter.

15 35. In combination, an instrument and an integral gripping device for aiding in the gripping of said instrument, said instrument having a barrel portion and an operating portion at an end of the instrument opposite said barrel portion for performing an operation, said gripping device comprising:

first and second ends respectively adjacent to said barrel portion and said operating portion;

20 a body of said gripping device between said first and second ends having a generally hour-glass shape on two opposing sides, one of said two opposing sides being expanded at said first end to form said support shelf for supporting a portion of a single finger;

25 two remaining sides of said device having generally linear surfaces extending in a longitudinal direction and having a convex surface when viewed in cross-section; and

30 said two remaining sides and a remaining one of the opposing sides having a generally hour-glass shape serving as single or plural finger support surfaces.

36. A combination according to claim 35 wherein said instrument is a writing instrument having an elongated tubular-shaped supply member arranged in said instrument and aligned at one end with said operating portion, which comprises a writing point, said tubular member being aligned so that its longitudinal axis is displaced from central a longitudinal axis of said barrel portion.

37. A combination according to claim 36 wherein said writing point is displaced from said support shelf so as to be positioned so that the longitudinal central axis of the instrument lies between said shelf and the longitudinal central axis of the tubular-shaped supply member.

38. The combination according to claim 36 further comprising a closing cap for sealing an open end of said barrel portion, said cap having an internal annular recess for receiving and properly positioning an end of said tubular member regardless of an angular orientation of said cap relative to said barrel portion.

ABSTRACT OF THE DISCLOSURE

An instrument holder, which may be separate from or integral with the instrument for persons with or without physical disabilities. A central bore enables insertion of instruments of varying shapes. Gripping surfaces include a compound bevel downward and with a decided right or left hand slope. Elements from a top palm rest to the lower planar surface are volute, forming a right or left hand spiral. At the rear, the palm rest curves aft and under terminating in the bevelled vertical detente. The hand specific side forms a concave surface sufficient to accommodate fingers, joints, knuckles, or hand webbing between finger joints, flaring outward joining the lower planar surface. From the upper rear bevel detente, the back forms a slightly convex surface connecting with the bottom. The body and instrument path is reversible exposing the larger circumference area of the palm rest along with other control surfaces. One version having an hour glass-shaped body with a truncated periphery forming a gripping surface with a curved concave surface portion enable the user to grip the device in any one of a variety of different ways.

03441-0430
46340-743430

FULL NAME: _____

ADDRESS: _____

() INDIVIDUAL () SMALL BUSINESS CONCERN
() NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

CARL BISTRACK
NAME OF INVENTOR

Carl Bistrack
SIGNATURE OF INVENTOR

4/25/94
DATE

2025-04-25 14:43:30

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled ADAPTABLE PRESSURING WRITING INSTRUMENT HOLDER, the specification of which:

(check one) X is attached hereto.
 was filed on _____
 as App.Ser.No. _____
 and was amended on _____
 (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign
Application(s)

Priority
Claimed

Number

Country

Day/Month/Year

Yes No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of the application:

<u>07/968,210</u>	<u>29 OCT. 1992</u>	<u>ABANDONED</u>
Application	Filing Date	Status
Serial Number		

<u>07/652,067</u>	<u>7 FEB. 1991</u>	<u>ABANDONED</u>
Application	Filing Date	Status
Serial Number		

<u>08/237,552</u>	<u>3 MAY 1994</u>	<u>PENDING</u>
Application	Filing Date	Status
Serial Number		

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

LOUIS WEINSTEIN, Reg. No. 20,477
WEINSTEIN, SCHER & KIMMELMAN

Address all telephone calls to LOUIS WEINSTEIN at telephone number: 215-928-4730.

Address all correspondence to:

Louis Weinstein
Weinstein, Scher & Kimmelman
The Curtis Center, Suite 750S
601 Walnut Street
Philadelphia, Pennsylvania 19106

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or
First Inventor: CARL BISTRACK

Inventor's
Signature: *Carl Bistrack*

Date: 4/25/97

Residence: ~~301 HEIGHTS LANE, APT. 15F~~
~~FEASTERVILLE, PENNSYLVANIA 19047~~

10013 JAMES ST #2
Philadelphia PA 19116

Citizenship: UNITED STATES OF AMERICA

Post Office Address: same as above

4/25/97

2025-04-25 14:00:00




FIG. 1




FIG. 1a




FIG. 2




FIG. 3




FIG. 3a




FIG. 4




FIG. 4a




FIG. 4b




FIG. 5




FIG. 6




FIG. 7




FIG. 7a








FIG. 8








FIG. 15a




FIG. 16




FIG. 16a











FIG. 17







F I G. 22




FIG. 23





FIG. 23A



F I G. 23C




FIG. 23B




FIG. 23D




FIG. 25




FIG. 24




FIG. 26




FIG. 27




FIG. 28




FIG. 28A




FIG. 28B





FIG. 28C






FIG. 30